



# Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 25kVA

By Acme Electric  
Catalog # T2535183S



Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 25kVA

## Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

## General

ANFC Taps	2
BNFC Taps	4
Catalog Number	T2535183S
Construction	Encapsulated
Electrostatic Shield	Shielded
Material Type	ZFIN
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	240 X 480
Product Category	Dry Type Distribution Transformer
Secondary Voltage	120/240 V
Taps % Steps	2.5%
UL Insulation Class	180°C
UPC	047503734209
Winding Material	AL
kVA	25

## Dimensions

Dimensions	13.34 in x 16.13 in x 18.44 in
Height	18.44 in
Length	13.34 in
Weight	250 lb
Width	16.13 in

## Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240 X 480 V

## Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

## Logistics

Carton Quantity	1
Pallet Quantity	4

## Product Assets

[Brochures - General Purpose Dry-Type Distribution Transformers](#)  
[Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers](#)  
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)  
[Customer Use Drawings - a-700322](#)  
[Customer Use Drawings - a-125881](#)  
[Customer Use Drawings - a-125877](#)  
[Customer Use Drawings - a-125893](#)  
[Customer Use Drawings - a-125853](#)  
[Customer Use Drawings - a-125883](#)  
[Customer Use Drawings - a-125873](#)  
[Customer Use Drawings - a-102722-b](#)  
[Customer Use Drawings - a-125885](#)  
[Engineering Drawing - T2535183S](#)  
[SDS - HCC SDS](#)  
[Specifications - T2535183S](#)  
[Terms and Conditions - HCC Terms & Conditions](#)