

## X-Hook Low Friction Cable Hooks



BCH64X

New Xylan<sup>®†</sup> coating reduces cable friction. Ideal for pulling cable.

- Xylan<sup>®†</sup> coating provides smooth frictionless surface for cable pulling.
- Great for use in corners, drop-outs or direction change.
- X-Hook has lower coefficient of friction than Teflon<sup>®†</sup>.
- Cable retainer clips are included with hooks.
- Static Load Capacity: 30 Lbs.




Cable rollers are too expensive and require installation and removal.

UPC/Part Number	Catalog Number	Hook Size	Capacity	Box Qty.
78205129940	<b>BCH21X</b>	1 <sup>5</sup> / <sub>16</sub> "	50 4-Pair UTP Cat 5e or 2-Strand Fiber Optic Cable or 32 CAT6 or 18 CAT6A	50
78205129941	<b>BCH32X</b>	2"	80 4-Pair UTP Cat 5e or 2-Strand Fiber Optic Cable or 50 CAT6 or 25 CAT6A	50
78205129942	<b>BCH64X</b>	4"	300 4-Pair UTP Cat 5e or 2-Strand Fiber Optic Cable or 185 CAT6 or 98 CAT6A	25

Note: For cable hook assemblies with X-Hooks add an X to the part number.

Example: BCH32X-U-2-4

(See pages 235-236 for technical data.)



<sup>†</sup> Xylan<sup>®</sup> is a registered trademark used by Whitford Corporation  
Teflon<sup>®</sup> is a registered trademark used by DuPont<sup>®</sup>

*Read safety/installation instruction sheets in packages before use.*