


## Grounding - Steel

### Images

[Download Photo Image](#)[Download Dimensional Image](#)

Dimension A in Inches: 2.74  
Dimension B in Inches: 4.22  
Dimension C in Inches: 0.73  
Dimension D in Inches: 3.37  
Dimension E in Inches: 4.50

### Application

Used in situations where wires have already been pulled through Rigid/IMC conduit, and an insulated Grounding bushing is required. Grounding lug, aluminum alloy 6061-T6. Rated 150 Degree C. cULus listed. Patented

### Product Information

Material: Steel  
Finish: Zinc Plated, Grounding Lug, Tin  
Electro-Plate

### Certifications & Codes:

Federal Specification Number: A-A-50553  
NEMA Standard: FB-1  
UL File Number: E20412  
UL Standard: UL-514B  
UNSPSC: 39121312

**Catalog ID:** SGBS-38940

**UPC Number:** 78174723895

**Description:** Split Bushing, Insulated, Grounding, Steel,  
Size 3-1/2 Inch, 6-250 Lug

**Application:** Used in situations where wires have already been pulled through Rigid/IMC conduit, and an insulated Grounding bushing is required. Grounding lug, aluminum alloy 6061-T6. Rated 150 Degree C. cULus listed. Patented

**Trade Size:** 3-1/2"

**Std Pkg Qty:** 25

**Unit Qty:** -