

AMS2, AL Set Screw Splice, #2-14 AWG, 2 Screws, Al/Cu Rated

By Burndy
Catalog # [AMS2](#)

Aluminum Mechanical Splice, 2-14 AWG, 3/8" Screw Dia, 2 Screws, Al/Cu Rated, Tin Plated



Features

- Standard mounting hole diameter is .562" for 1/2" bolts
- The end wall within the cable socket of this design is solid and pressure tight
- Connectors are pre-filled and plugged with electrical joint compound
- Marked with catalog number, conductor size and die reference
- Meets performance requirements of ANSI C119.4

Application

For Use With Copper And Aluminum Conductors

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Industry Standard(s)	ANSI C119.4
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - ACSR Cmpt Size	2 AWG
Conductor - Copper Str Size	2 AWG-1 AWG
Conductor - ACSR Str Size	2 AWG-1 AWG
Conductor - AL Str Run	<ul style="list-style-type: none"> • 12 AWG • 10 AWG • 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - AL Str Run Range	12 AWG-2 AWG
Conductor - AL Str Size	<ul style="list-style-type: none"> • 12 AWG • 10 AWG • 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - AL Str Size Range	12 AWG-2 AWG

Conductor - AL Str Tap	<ul style="list-style-type: none"> • 12 AWG • 10 AWG • 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - AL Str Tap Range	12 AWG-2 AWG
Conductor - Copper Solid Run	<ul style="list-style-type: none"> • 14 AWG • 13 AWG • 12 AWG • 11 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - Copper Solid Run Range	14 AWG-2 AWG
Conductor - Copper Solid Size	<ul style="list-style-type: none"> • 12 AWG • 11 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - Copper Solid Size Range	12 AWG-2 AWG
Conductor - Copper Solid Tap	<ul style="list-style-type: none"> • 14 AWG • 13 AWG • 12 AWG • 11 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG

Conductor - Copper Solid Tap Range	<ul style="list-style-type: none"> • 3 AWG • 2 AWG 14 AWG-2 AWG
Conductor - Copper Str Compact Size	2 AWG
Conductor - Copper Str Run	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - Copper Str Run Range	14 AWG-2 AWG
Conductor Size	14-2 AWG
Conductor - Copper Str Size Range	14 AWG-2 AWG
Conductor - Copper Str Tap	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - Copper Str Tap Range	14 AWG-2 AWG

Configuration

Physical Attribute - Number of Screws	2
Connector Type	In-Line

Current

Rating - Minimum Voltage	600
--------------------------	-----

Dimensions

Package Length	3.800 in
Package Width	3.300 in
Package Weight	0.400 lb.
Die Size	<ul style="list-style-type: none"> • EEI 11A

Dimension - L Length Overall mm	40 mm
Dimension - H1 Height inch	0.56 in
Dimension - Height fraction	9/16
Package Height	3.300 in
Dimension - Height mm	0 mm
Width	0.56 in
Dimension - Width fraction	9/16 in
Dimension - Width inch	0.56 in
Dimension - Width mm	14 mm
Depth	0.56 in
Length	1.59 in
Hex Size	Slot
Dimension - Length Overall inch	1.59 in
Height	0.79 in
Dimensions	1.59 in x 0.56 in x 0.79 in

Force Related

Installation Torque Recommended in-lb	50 LBS/in
---------------------------------------	-----------

General

Material - Hardware	Aluminum
Sub Brand	SPLICER/REDUCER
Physical Attribute - Screw Type	Slot
Plated	Y
Type	AMS, Dual Rated
UPC 12 Digit	781810241004
UPC 14 Digit GTIN	00781810241004
Material	Aluminum
Plating Type	Tin
UPC	781810241004

Logistics

Minimum Pack Quantity	1
Carton Quantity	360
Pallet Quantity	11520

Operational

Temperature Rating	194° F
--------------------	--------

Product Assets

[Catalog \[English\]](#)

