


ASA1000U, Terminal Stacking Adaptor, Al/Cu, 1000 kcmil

By Burndy
Catalog # [ASA1000U](#)



Terminal Stacking Adaptor, Al/Cu, Tin Plated

Features

- For use on terminals made from copper or aluminum
- May be used with standard NEMA two and four hole terminals
- TO stack four hole NEMA terminations use two stacking adaptors assembled side-by-side
- Only three sizes necessary to accommodate terminals from 250 kcmil through 1000 kcmil

Application

For Aluminum And Copper Terminals

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil;700 kcmil;750 kcmil;800 kcmil;850 kcmil;900 kcmil;1000 kcmil
Conductor - AL Str Size	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil;550 kcmil;556 kcmil;600 kcmil;636 kcmil;650 kcmil;700 kcmil;715 kcmil;750 kcmil;795 kcmil;800 kcmil;874 kcmil;900 kcmil;954 kcmil;1000 kcmil
Conductor - AL Str Size Range	1/0 AWG-1000 kcmil
Conductor - Copper Str Size Range	1/0 -1000 kcmil

Conductor Type AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Holes	2
Physical Attribute - Number of Screws	2

Current

Rating - Minimum Voltage 600

Dimensions

Dimension - L Length Overall mm	23 mm
Dimension - Pad Width inch	1.25 in
Dimension - Height fraction	1-1/4 in
Dimension - Height inch	1.25 in
Dimension - Height mm	31.8 mm
Width	1.25 in
Length	3 in
Dimension - Bolt Size inch	3.75 in
Dimension - Length Overall inch	0.91 in
Height	1.25 in
Dimensions	3 in x 1.25 in x 1.25 in

Force Related

Installation Torque Recommended in-lb 480 LBS/in

General

Material - Hardware	DURIUM™ Silicon Bronze
Trade Name	HYSTACK™
Sub Brand	HYSTACK
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	Y
Type	Stacking Adaptors
UPC 12 Digit	781810521045
UPC 14 Digit GTIN	00781810521045
Material	Aluminum
Plating Type	Tin
UPC	781810521045

Logistics

Minimum Pack Quantity 1

Carton Quantity 10
Pallet Quantity 4640

Temperature Rating 194° F

Product Assets

Operational

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-ASA1000U-SPEC-EN | REV 11/2025