



**ASA250U, Terminal Stacking Adapter,
Al/Cu, 2-Slot, 250 kcmil**

By Burndy
Catalog # [ASA250U](#)

Terminal Stacking Adaptor, Al/Cu, Tin Plated



Features

- For use on terminals made from copper or aluminum
- May be used with standard NEMA two and four hole terminals
- TO stack four hole NEMA terminations use two stacking adapters assembled side-by-side
- Only three sizes necessary to accommodate terminals from 250 kcmil through 1000 kcmil

Application

For Aluminum And Copper Terminals

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Buy America(n) Qualified Certification - ETL	No
Standards - RoHS Compliance Status	Contact Manufacturer
Certification - CSA Approved	CM
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes
	No

Conductor

Conductor - Copper Str Size	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - AL Str Size	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - AL Str Size Range	1/0 AWG-250 kcmil
Conductor - Copper Str Size Range	1/0 -250 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Holes	2
Physical Attribute - Number of Screws	2

Current

Rating - Minimum Voltage	600
--------------------------	-----

Dimensions

Dimension - Outside Diameter inch	0.87 in
Dimension - L Length Overall mm	20 mm
Dimension - Pad Width inch	1.00 in
Dimension - Height fraction	7/9 in
Dimension - Height inch	0.77 in
Dimension - Height mm	19.6 mm
Width	1 in
Length	3 in
Dimension - Bolt Size inch	2.75 in
Dimension - Length Overall inch	0.78 in
Height	0.77 in
Dimensions	3 in x 1 in x 0.77 in

Force Related

Installation Torque Recommended in-lb	480 LBS/in
---------------------------------------	------------

General

Material - Hardware	DURIUM™ Silicon Bronze
Trade Name	HYSTACK™
Sub Brand	HYSTACK
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	Y
Type	Stacking Adapters
UPC 12 Digit	781810521007
UPC 14 Digit GTIN	00781810521007
Material	Aluminum
Plating Type	Tin
UPC	781810521007

Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	4640

Operational

Temperature Rating	194° F
--------------------	--------

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-ASA250U-SPEC-EN | REV 11/2025