


ASA800U, Terminal Stacking Adapter, Al/Cu, 2-Slot, 800 kcmil

By Burndy
Catalog # [ASA800U](#)



Terminal Stacking Adaptor, Al/Cu, Tin Plated

Features

- For use on terminals made from copper or aluminum
- May be used with standard NEMA two and four hole terminals
- TO stack four hole NEMA terminations use two stacking adapters assembled side-by-side
- Only three sizes necessary to accommodate terminals from 250 kcmil through 1000 kcmil

Application

For Aluminum And Copper Terminals

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil;700 kcmil;750 kcmil;800 kcmil
Conductor - AL Str Size	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil;550 kcmil;556 kcmil;600 kcmil;636 kcmil;650 kcmil;700 kcmil;715 kcmil;750 kcmil;795 kcmil;800 kcmil
Conductor - AL Str Size Range	1/0 AWG-800 kcmil
Conductor - Copper Str Size Range	1/0 -800 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Holes 2

Physical Attribute - Number of Screws 2

Current

Rating - Minimum Voltage 600

Dimensions

Dimension - L Length Overall mm	20 mm
Dimension - Pad Width inch	1.00 in
Dimension - Height fraction	1-1/8 in
Dimension - Height inch	1.13 in
Dimension - Height mm	28.7 mm
Width	1 in
Length	3 in
Dimension - Bolt Size inch	3.50 in
Dimension - Length Overall inch	0.78 in
Height	1.13 in
Dimensions	3 in x 1 in x 1.13 in

Force Related

Installation Torque Recommended in-lb 480 LBS/in

General

Material - Hardware	DURIUM™ Silicon Bronze
Trade Name	HYSTACK™
Sub Brand	HYSTACK
Physical Attribute - Screw Type Plated	Hexagonal Bolt Y
Type	Stacking Adapters
UPC 12 Digit	781810521021
UPC 14 Digit GTIN	00781810521021
Material	Aluminum
Plating Type	Tin
UPC	781810521021

Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	4640

Operational

Temperature Rating 194° F

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-ASA800U-SPEC-EN | REV 11/2025