



## B2D12 Copper Braid, 12" Long, 2 Braids, 2 Holes 2 Ferrules, 7/16" Stud, 1-1/4" Stud Hole Spacing, 380 amps Indoor, 455 amps Outdoor

By Burndy  
Catalog # [B2D12](#)



Copper Braid, 12" Long, 2 Braids, 2 Holes 2 Ferrules, 7/16" Stud, 1-1/4" Stud Hole Spacing, 380 amps Indoor, 455 amps Outdoor.

### Application

Flexible copper braid jumpers designed to take up linear expansion and contraction, compensate for misalignment and absorb vibratory movement of electrical equipment and devices

### General

Catalog Number	B2D12
Connector Type	Braid
EU RoHS Indicator	Yes
Material	Copper
Material - Ferrules	Y
Physical Attribute - Number of Braids	2
Plated	Y
Sub Brand	BRAID
Type	B, Flexible
UPC	781810807002
UPC 12 Digit	7818108070022

### Dimensions

Dimension - D inch	2.5
Dimension - Hole Size inch	0.44
Dimension - L Length Overall mm	305 mm
Dimension - Length Overall inch	12.00 in
Dimension - N inch	0.62
Dimension - Pad Width inch	0.94
Length	12 in

### Electrical Ratings

Rating - Indoor Amperage	380
Rating - Outdoor Amperage	455

### Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry	UL467
Standards Met	
Standards - RoHS Compliance Status	CM
UL Listed	Yes

### Logistics

Minimum Pack Quantity	1
-----------------------	---

### Product Assets

<a href="#">3D Models - B2D12_MODEL-IGES</a>
<a href="#">3D Models - B2D12_MODEL-STEP</a>
<a href="#">3D Models - B2D12_MODEL-PDF</a>
<a href="#">Catalogs - Full Line BURNDY Catalog</a>
<a href="#">Catalogs - Section E2 - Mechanical Grounding</a>
<a href="#">Customer Notices - Prop 65 Notice</a>
<a href="#">Product Cross Section Image(s) - BUR_BD_Lineart</a>
<a href="#">Sales Drawings - SE210201-02_DL</a>



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-B2D12-SPEC-EN | REV 6/2024