

B2D12N Flexible Copper Braid

By Burndy Catalog # B2D12N

Cu Flexible Braid, 2-NEMA Holes 2 Ferrules, 12.00" L, 0.56" Hole Dia.



Features

- Most Burndy braid are UL Listed and CSA Certified
- Pressed seamless copper ferrules provide added durability and prevent fraying, providing extra strength for a robust bonding connection
- Braid is especially suited for applications that require flexibility or resistance to vibration
- Extra fine stranding gives enhanced flexibility
- Ferrules clearly marked with Burndy braid type and UL markings (where appropriate)
- Available in custom lengths and hole sizes to suit your needs (contact your local sales representative for non-standard configurations)
- For assistance in finding the perfect braid for your needs click here for our Braid Configurator Tool: www.hubbell.com/config/BRAID

General

Catalog Number	B2D12N
Connector Type	Braid
Material	Copper
Material - Ferrules	Υ
Physical Attribute - Number of	2
Braids	

Plated Y

UPC 781810004937 UPC 14 Digit GTIN 00781810004937

Dimensions

Dimension - D inch	3.00 in
Dimension - Hole Size inch	0.56 in
Dimension - L Length Overall	305 mm

mm

Dimension - Length Overall	12.00 in
inch	
Dimension - N inch	0.62 in
Dimension - Pad Width inch	0.94 in
Length	12.2 in

Electrical Ratings

Rating - Indoor Amperage	380
Rating - Outdoor Amperage	455

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards	UL467
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Logistics

Minimum Pack Quantity

Product Assets

Catalogs - Burndy Grounding Catalog
Catalogs - BURNDY Master Catalog - Section E2 - Mechanical
Grounding
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_BD_Lineart
Sales Drawings - SE210201-02 DI

Specifications - B2D12N