

## B3F12N Flexible Copper Braid

By Burndy  
Catalog # [B3F12N](#)

Cu Flexible Braid Jumper, 2 Holes 2 Ferrules, 1.75" Spacing,  
12.00" L, Amp Rating: 820(Indoor) 980(Outdoor).



### Features

- Most Burndy braid are UL Listed and CSA Certified
- Pressed seamless copper ferrules provide added durability and prevent fraying, providing extra strength for a robust bonding connection
- Braid is especially suited for applications that require flexibility or resistance to vibration
- Extra fine stranding gives enhanced flexibility
- Ferrules clearly marked with Burndy braid type and UL markings (where appropriate)
- Available in custom lengths and hole sizes to suit your needs (contact your local sales representative for non-standard configurations)
- For assistance in finding the perfect braid for your needs click [here](http://www.hubbell.com/config/BRAID) for our Braid Configurator Tool:

### General

Catalog Number	B3F12N
Material	Copper
Material - Ferrules	Y
Physical Attribute - Number of Braids	3
UPC	781810005064
UPC 14 Digit GTIN	00781810005064

### Dimensions

Dimension - D inch	3.00 in
--------------------	---------

Dimension - Hole Size inch	0.56 in
Dimension - N inch	0.62 in
Dimension - Pad Width inch	1.44 in
Length	12 in

### Electrical Ratings

Rating - Indoor Amperage	820
Rating - Outdoor Amperage	980

### Certifications And Compliance

Standards - RoHS Compliance Status	CM
UL Listed	Yes

### Logistics

Carton Quantity	1
Minimum Pack Quantity	1

### Product Assets

- [Catalogs - Burndy Grounding Catalog](#)
- [Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_BD\\_Lineart](#)
- [Sales Drawings - SE212301-01](#)
- [Specifications - B3F12N](#)