

By Burndy
 Catalog # [BB024L9T14](#)

Flexible Copper Braid, 9.00 in, Flexible copper braid jumpers designed to take up linear expansion and contraction



Features

- Most Burndy braid are UL Listed and CSA Certified
- Pressed seamless copper ferrules provide added durability and prevent fraying, providing extra strength for a robust bonding connection
- Braid is especially suited for applications that require flexibility or resistance to vibration
- Extra fine stranding gives enhanced flexibility
- Ferrules clearly marked with Burndy braid type and UL markings (where appropriate)
- Available in custom lengths and hole sizes to suit your needs (contact your local sales representative for non-standard configurations)
- For assistance in finding the perfect braid for your needs click here for our Braid Configurator Tool: www.hubbell.com/config/BRAID

Application

Flexible copper braid jumpers designed to take up linear expansion and contraction

Specifications

Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Configuration

Connector Type	Braid
----------------	-------

Current

Rating - Indoor Amperage	93
Rating - Outdoor Amperage	93

Dimensions

Dimension - L Length Overall mm	229 mm
Dimension - Stud Size inch Length	1/4 9 in
Dimension - Length Overall inch	9.00 in
Dimension - N inch	0.5 in

General

Material - Ferrules	Y
Sub Brand	BRAID
Physical Attribute - Number of Braids	1
Type	B
UPC 12 Digit	781810552537
UPC 14 Digit GTIN	00781810552537
Material	Copper
UPC	781810552537

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	2250

Product Assets

[Catalog \[English\]](#)