



BDBMHC113501, 1-Pole Power Distribution Block

By Burndy
Catalog # [BDBMHC113501](#)

Terminal block covers, AWG 6 - 350 kcmil (Run), AWG 6 - 350 kcmil (Tap), Power Distribution Block, 1.85 W, 3.25 H



Features

- VERSIPOLE Configurable Power Distribution Blocks
- Available in 3 sizes for optimization of space
- Suitable for use with aluminum or copper conductors
- Single or dual run connections
- 600V Al/Cu Rated
- High short-circuit rating up to 100kA with proper fusing
- Adders and end barriers available separate for all 3 sizes

Specifications

Certification - cULus	No
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - Copper Str Run	6;5;4;3;2;1;1/0;2/0;3/0;4/0;250;300;350
Conductor - Copper Str Run Range	6-350
Conductor - Copper Str Tap	6;5;4;3;2;1;1/0;2/0;3/0;4/0;250;300;350
Conductor - Copper Str Tap Range	6-350
Conductor Type	AL C Str-Run;CU C Str-Run;AL C Str-Tap;CU C Str-Tap
Conductor - AL Str Run	6;4;3;2;1;1/0;2/0;3/0;4/0;250;266.8;300;336.4;350
Conductor - AL Str Run Range	6-350
Conductor - AL Str Tap	6;4;3;2;1;1/0;2/0;3/0;4/0;250;266.8;300;336.4;350
Conductor - AL Str Tap Range	6-350

Configuration

Number Of Poles	1
-----------------	---

Current

Rating - Minimum Voltage	600
Amperage Rating	310 A

Dimensions

Dimension - Width inch	1.85 in
Dimension - Width mm	47 mm
Dimension - L Length Overall mm	127 mm
Dimension - Height inch	3.25 in
Dimension - Height mm	82.6 mm
Length	1.85 in
Dimension - Length Overall inch	5.00 in
Width	3.88 in
Height	3.25 in
Dimensions	1.85 in x 3.88 in x 3.25 in

General

Trade Name	VERSIPOLE™
Plated	Y
Insulation	Y
UPC 12 Digit	781810645697
UPC 14 Digit GTIN	00781810645697
Material	Aluminum
Plating Type	Tin
UPC	781810645697

Logistics

Minimum Pack Quantity	1
Carton Quantity	18
Pallet Quantity	1

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)