

BDBMHC222/01, 1-Pole Power Distribution Block

By Burndy

Catalog # [BDBMHC222/01](#)

Terminal block covers, AWG 14 - 2/0 (Run), AWG 14 - 2/0 (Tap), Power Distribution Block, Hex size:3/16(Run), 3/16(Tap)



Features

- VERSIPOLE Configurable Power Distribution Blocks
- Available in 3 sizes for optimization of space
- Suitable for use with aluminum or copper conductors
- Single or dual run connections
- 600V Al/Cu Rated
- High short-circuit rating up to 100kA with proper fusing
- Adders and end barriers available separate for all 3 sizes

Application

Suitable for use with aluminum or copper conductors providing maximum versatility

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - AL Str Run	12;10;8;6;4;3;2;1;1/0;2/0
Conductor - AL Str Run Range	12-2/0
Conductor - AL Str Tap	12;10;8;6;4;3;2;1;1/0;2/0
Conductor - AL Str Tap Range	12-2/0
Conductor - Copper Str Run	14;12;10;9;8;7;6;5;4;3;2;1;1/0;2/0
Conductor - Copper Str Run Range	14-2/0
Conductor - Copper Str Tap	14;12;10;9;8;7;6;5;4;3;2;1;1/0;2/0
Conductor - Copper Str Tap Range	14-2/0
Conductor Type	AL C Str-Run;CU C Str-Run;AL C Str-Tap;CU C Str-Tap

Configuration

Number Of Poles	1
-----------------	---

Current

Rating - Minimum Voltage	600
Amperage Rating	350 A

Dimensions

Dimension - L Length Overall	127 mm
Dimension - Height inch	3.25 in
Dimension - Height mm	82.6 mm
Width	3.88 in
Dimension - Width inch	1.85 in
Dimension - Width mm	47 mm
Length	1.85 in
Dimension - Length Overall	5.00 in
inch	
Height	3.25 in
Dimensions	1.85 in x 3.88 in x 3.25 in

General

Trade Name	VERSIPOLE™
Insulation	Y
Sub Brand	VERSIPOLE
Plated	Y
Type	BDBMH
UPC 12 Digit	781810645901
UPC 14 Digit GTIN	00781810645901
Material	Aluminum
Plating Type	Tin
UPC	781810645901

Logistics

Minimum Pack Quantity	1
Carton Quantity	18
Pallet Quantity	864

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)