



## BG12N Flexible Copper Braid, 12 in L, Approximate Ampere rating indoor:415, outdoor:495

By Burndy  
Catalog # [BG12N](#)

Flexible Copper Braid, 12 in L, Approximate Ampere rating indoor:415, outdoor:495.



### Application

Flexible copper braid jumpers designed to take up linear expansion and contraction

### General

Catalog Number	BG12N
Connector Type	Braid
EU RoHS Indicator	Yes
Material	Copper
Material - Ferrules	Y
Physical Attribute - Number of Braids	1
Plated	Y
Sub Brand	BRAID
Type	B, Flexible
UPC	781810005323
UPC 12 Digit	7818100053233

### Dimensions

Dimension - D inch	3.00 in
Dimension - Hole Size inch	0.56 in
Dimension - L Length Overall mm	305 mm
Dimension - Length Overall inch	12.00 in
Dimension - N inch	0.62 in
Dimension - Pad Width inch	1.50 in
Length	12 in

### Electrical Ratings

Rating - Indoor Amperage	415
Rating - Outdoor Amperage	495

### Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry	UL467
Standards Met	
Standards - RoHS Compliance Status	CM
UL Listed	Yes

### Logistics

Minimum Pack Quantity	1
-----------------------	---

### Product Assets

<a href="#">3D Models - BG12N_MODEL-PDF</a>
<a href="#">3D Models - BG12N_MODEL-STEP</a>
<a href="#">3D Models - BG12N_MODEL-IGES</a>
<a href="#">Catalogs - Full Line BURNDY Catalog</a>
<a href="#">Catalogs - Section E2 - Mechanical Grounding</a>
<a href="#">Customer Notices - Prop 65 Notice</a>
<a href="#">Product Cross Section Image(s) - BUR_BD_Lineart</a>
<a href="#">Sales Drawings - SE..210201-01</a>



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-BG12N-SPEC-EN | REV 6/2024