

BIBD2/02, Double Sided Two Conductor Clear Insulated Mult-Tap Connector

By Burndy
Catalog # [BIBD2/02](#)

Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 2 Sided Entry, 14-2/0 AWG, Al/Cu Rated



Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 Str
Conductor - AL Str Size	<ul style="list-style-type: none"> • 8 AWG

- 6 AWG
- 4 AWG
- 3 AWG
- 2 AWG
- 1 AWG
- 1/0 AWG
- 2/0 AWG

Conductor - AL Str Size Range	8 AWG-2/0 AWG
Conductor Size	14-2/0 AWG
Conductor - Copper Str Size Range	14 AWG - 2/0 AWG
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size

Configuration

Physical Attribute - Number of Screws	2
Connector Type	Multi Tap
Number Of Ports	2

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Dimension - L Length Overall mm	39 mm
Dimension - Height fraction	1.375 in
Dimension - Height inch	1.38 in
Dimension - Height mm	35.1 mm
Dimension - Width fraction	1-14/25 in
Dimension - Width inch	1.56 in
Dimension - Width mm	40 mm
Physical Attribute - Socket Size	0.19
Dimension - Length Overall inch	1.52 in

General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIBD, Multi-Port

UPC 12 Digit	781810223932
UPC 14 Digit GTIN	00781810223932
Material	Aluminum
Hex Key	3/16
Plating Type	Unplated
UPC	781810223932

Carton Quantity	100
Pallet Quantity	9600

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)

[Catalog \[English\]](#)

Logistics

Minimum Pack Quantity	1
-----------------------	---



A Hubbell brand