



BIBD6006, Double Sided Six Conductor Clear Insulated Mult-Tap Connector

By Burndy
Catalog # [BIBD6006](#)

Aluminum Multiple Tap Connector, Clear Insulated, 6 Port, 2 Sided Entry, 4 AWG-600 kcmil, Al/Cu Rated



Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil • 500 kcmil • 550 kcmil
-----------------------------	---

Conductor - AL Str Size

- 600 kcmil
- 4 AWG
- 3 AWG
- 2 AWG
- 1 AWG
- 1/0 AWG
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil
- 266 kcmil
- 300 kcmil
- 336 kcmil
- 350 kcmil
- 397 kcmil
- 400 kcmil
- 450 kcmil
- 477 kcmil
- 500 kcmil
- 550 kcmil
- 556 kcmil
- 600 kcmil

Conductor - AL Str Size Range

4 AWG - 600 kcmil

Conductor Size

4 AWG-600 KCMIL

Conductor - Copper Str Size Range

4 AWG - 600 kcmil

Conductor Type

- AL C Str-Size
- CU C Str-Size

Configuration

Physical Attribute - Number of Screws	6
Connector Type	Multi Tap
Number Of Ports	6

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Dimension - L Length Overall mm	199 mm
Dimension - Height fraction	2.75 in
Dimension - Height inch	2.75 in
Dimension - Height mm	69.9 mm
Dimension - Width inch	3.00 in
Dimension - Width mm	76 mm

Dimension - Length Overall
inch 7.84 in

Hex Key 3/8
Plating Type Unplated
UPC 781810224182

General

Material - Hardware Aluminum
Insulation Type Platisol
Trade Name UNITAP™
Insulation Y
Sub Brand UNITAP
Physical Attribute - Screw Type Allen
Plated N
Type BIBD, Multi-Port
UPC 12 Digit 781810224182
UPC 14 Digit GTIN 00781810224182
Material Aluminum

Logistics

Minimum Pack Quantity 1
Carton Quantity 25
Pallet Quantity 375

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)



A Hubbell brand