

BIBS3502DB, Direct Burial Submersible Two Conductor Insulated Multi-Tap Connector

By Burndy
Catalog # [BIBS3502DB](#)



Direct Burial UNITAP™, 350 Kcmil -12 AWG Str., 2.61 in L,
Designed specifically for direct burial applications.

Features

- Dual rated for aluminum or copper conductors
- Each unit individually marked for ease of identification
- Supplied with aluminum set-screws
- Supplied with oxide inhibitor pre-installed
- Submersible rated and suitable for Direct Burial

Application

For Outside Direct Burial

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - AL Str Size Range	12 AWG - 350 kcmil
Conductor Size	12 AWG-350 KCMIL
Conductor - Copper Str Size Range	12 AWG - 350 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Connector Type	Multi Tap
Number Of Ports	2

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Dimension - L Length Overall	66 mm
Dimension - Height inch	2.46 in
Dimension - Height mm	62.5 mm
Dimension - Strip Length inch	1.125
Dimension - Width inch	4.06 in
Dimension - Width mm	103 mm
Dimension - Length Overall	2.61 in

Force Related

Installation Torque	450 LBS/in
Recommended in-lb	

General

Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Plated	N
Type	BIBS, Multi-Port - Direct Burial
UPC 12 Digit	781810523582
UPC 14 Digit GTIN	00781810523582
Material	Aluminum
Plating Type	Unplated
UPC	781810523582

Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	768

Operational

Temperature Rating	194
--------------------	-----

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)