



BURNDY Catalog Number BIBS5004DB
UPC Number 781810523643
Description 500-10 DB UNITAP 4 PORT
Status Active

Web Use
BURNDY Product Line

Dimensional	
Width (in)	4.58
Length (in)	5.69
Height (in)	3.13
Electrical	
Min Voltage Rating	600
General	
Number of Ports	4
Product Description	Multi Port Direct Burial, 4 Ports, 500 kcmil-12 AWG Str, 600 V
Conductor(s)	
Aluminum Size (Range)	10 AWG-500 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	10 AWG-500 kcmil
Physical	
Installation Torque	550
Type of Plating	Unplated
Plated (Yes or No)	N
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL486D
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies

47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175