


BIPC4/06, Insulating Piercing Connector - Discontinued

By Burndy
Catalog # [BIPC4/06](#)



BURNDY Insulation Piercing Connector

Features

- This item is discontinued, please see BIPC2504SC as a suggested alternate

Application

For Splicing And Tapping Aluminum And Copper Conductors

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - AL Str Run Range	1/0 AWG-4/0 AWG
Conductor - AL Str Tap Range	6-1/0 AWG
Conductor - Copper Str Run Range	1/0 -4/0 AWG
Conductor - Copper Str Tap Range	6 AWG-1/0
Conductor Type	AL C Str-Run;CU C Str-Run;AL C Str-Tap;CU C Str-Tap

Configuration

Physical Attribute - Number of Screws	2
Connector Type	Insulation Piercing

Current

Voltage - Maximum	300 V
Rating - Minimum Voltage	600

Dimensions

Dimension - L Length Overall	54 mm
Dimension - Height inch	2.50 in
Dimension - Height mm	63.5 mm
Dimension - Width inch	2.00 in
Dimension - Width mm	51 mm
Physical Attribute - Socket Size	1/2
Dimension - Bolt Size inch	0.31 in
Dimension - Length Overall	2.12 in

Force Related

Installation Torque Recommended in-lb	250 LBS/in
---------------------------------------	------------

General

Sub Brand	INSULATION PIERCING CONNECTOR
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Type	BIPC
UPC 12 Digit	781810128718
UPC 14 Digit GTIN	00781810128718
Material	Aluminum
Plating Type	Unplated
UPC	781810128718

Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	3552

Product Assets

[Catalog \[English\]](#)