

BIT350, Single Sided Two Conductor Clear Insulated Multi-Tap Connector

By Burndy
Catalog # [BIT350](#)

Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 1 Sided Entry, 10 AWG-350 kcmil, Al/Cu Rated



Features

- Type BIT and BITO (Offset) Multi-tap connectors are installed quickly and easily
- Suitable for use on Code conductor
- UL486B Listed, Dual-rated AL9CU.

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil
Conductor - AL Str Size	<ul style="list-style-type: none"> • 8 AWG • 6 AWG

- 4 AWG
- 3 AWG
- 2 AWG
- 1 AWG
- 1/0 AWG
- 2/0 AWG
- 3/0 AWG
- 4/0 AWG
- 250 kcmil

Conductor - AL Str Size Range	10 AWG - 350 kcmil
Conductor Size	10 AWG-350 KCMIL
Conductor - Copper Str Size Range	10 AWG - 350 kcmil
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size

Configuration

Physical Attribute - Number of Screws	2
Connector Type	Multi Tap
Number Of Ports	2

Current

Voltage - Maximum	600 V
Operating Voltage	600 V

Dimensions

Dimension - L Length Overall mm	56 mm
Dimension - Height fraction	2.5 in
Dimension - Height inch	2.5 in
Dimension - Height mm	64 mm
Dimension - Width fraction	2-8/25 in
Dimension - Width inch	2.32 in
Dimension - Width mm	59 mm
Dimension - Length Overall inch	2.22 in

General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen

Plated	N
Type	BIT
UPC 12 Digit	781810133538
UPC 14 Digit GTIN	00781810133538
Material	Aluminum
Hex Key	5/16 in
Plating Type	Unplated
UPC	781810133538

Minimum Pack Quantity	1
Carton Quantity	60
Pallet Quantity	2160

Operational

Temperature Rating	90 °C
--------------------	-------

Product Assets

[Catalog \[English\]](#)

[Catalog \[English\]](#)

Logistics



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-BIT350-SPEC-EN | REV 12/2025