


BIT4, Single Sided Two Conductor Clear Insulated Multi-Tap Connector

By Burndy
Catalog # [BIT4](#)

Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 1 Sided Entry, 14-4 AWG, Al/Cu Rated



Features

- Type BIT and BITO (Offset) Multi-tap connectors are installed quickly and easily
- Suitable for use on Code conductor
- UL486B Listed, Dual-rated AL9CU.

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	<ul style="list-style-type: none"> • Buy America Compliant (All status valid till December 2025) • Buy American Act Compliant (All status valid till December 2025) • BABA Compliant (All status valid till December 2025)
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG
Conductor - AL Str Size	<ul style="list-style-type: none"> • 8 AWG • 6 AWG • 4 AWG
Conductor - AL Str Size Range	14 AWG - 4 AWG
Conductor Size	14-4 AWG

Conductor - Copper Str Size Range	14 AWG - 4 AWG
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size

Configuration

Physical Attribute - Number of Screws	2
Connector Type	Multi Tap
Number Of Ports	2

Current

Voltage - Maximum	600 V
Operating Voltage	600 V

Dimensions

Dimension - L Length Overall mm	27 mm
Dimension - Height inch	1.25 in
Dimension - Height mm	32 mm
Dimension - Width fraction	1-4/25 in
Dimension - Width inch	1.16 in
Dimension - Width mm	29 mm
Dimension - Length Overall inch	1.08 in

Force Related

Installation Torque Recommended in-lb	45 in-lb
---------------------------------------	----------

General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIT
UPC 12 Digit	781810134146
UPC 14 Digit GTIN	00781810134146
Material	Aluminum
Hex Key	1/8 in
Plating Type	Unplated
UPC	781810134146

Logistics

Minimum Pack Quantity	1
Carton Quantity	250
Pallet Quantity	16000

Temperature Rating

90 °C

Product Assets

[Catalog \[English\]](#)

[Catalog \[English\]](#)

Operational



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-BIT4-SPEC-EN | REV 12/2025