



CL501, Copper Lay-in Lug

By Burndy
Catalog # [CL501](#)

Copper Lay-in Lug, 14-4 AWG, #10 Stud



Features

- UL467 Listed, Rated for Direct Burial
- Lay-In QIKLUG™ features high strength pure electrolytic copper ensuring maximum strength and conductivity
- Open-faced design allows for fast lay-in of conductor without the need for cutting or breaking

Application

For Direct Burial Applications In Concrete Or Earth, For Fast Lay-In Of The Conductor Without The Need For Cutting Or Breaking

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	Yes
EU RoHS Indicator	Yes
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none">• 14 AWG• 12 AWG• 10 AWG• 9 AWG• 8 AWG• 7 AWG• 6 AWG• 5 AWG• 4 AWG
Conductor - Copper Solid Size	<ul style="list-style-type: none">• 14 AWG• 13 AWG• 12 AWG• 11 AWG• 10 AWG• 9 AWG• 8 AWG• 7 AWG• 6 AWG

- 5 AWG
- 4 AWG

Conductor - Copper Solid Size Range	14 AWG-4 AWG
Conductor - Copper Str Size Range	14 AWG - 4 AWG
Conductor Type	CU C Str-Size

Dimensions

Package Length	5.500 in
Package Width	3.800 in
Package Weight	4.590 lb.
Dimension - L Length Overall mm	29 mm
Dimension - Height inch	0.85 in
Package Height	3.000 in
Dimension - Height mm	21.6 mm
Dimension - Hole Size inch	0.22 in
Dimension - Hole Size mm	6 mm
Dimension - Stud Size inch	17/64
Dimension - Width inch	0.38 in
Dimension - Width mm	10 mm
Dimension - Length Overall inch	1.13 in
Dimension - D inch	0.47 in
Dimension - N inch	0.19 in

General

Trade Name	QIKLUG™
Plated	N
Type	Open-Faced
UPC 12 Digit	781810276150
UPC 14 Digit GTIN	00781810276150
Material	Copper
Plating Type	Unplated
UPC	781810276150

Logistics

Minimum Pack Quantity	1
Carton Quantity	500
Pallet Quantity	25600

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)

