

CUSA442NTC, 2-Hole Copper Stacking Adapter, 1/2" Stud, 1-3/4" Spacing

By Burndy
Catalog # CUSA442NTC



Copper, tin plated, 2 hole (1/2" stud - 1-3/4" hole spacing), up to 35kV, used to elevate terminals for vertical parallel conductor accommodates. Adapter length 3.00", width 1.12", height 1.50

Features

- For use on terminals made from copper
- Designed specifically for stacking standard terminals, uses include placing the stacking adapter on the mounting plate and a terminal on top of the stack adapter and bolt down, or placing a stacking adapter on a terminal pad that will be mounted to a bus bar or mounting plate and a terminal on top of the stacking adapter, and bolt down
- May be used with standard NEMA two and four hole terminals, to stack four hole NEMA terminations requires use of two stacking adapters assembled side-by-side
- Stacking adapters are clearly marked

Application

Stacking Adapter

General

Catalog Number	CUSA442NTC
Connector Type	STACKING ADAPTER
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Physical Attribute - Number of Holes	2
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	STACKING ADAPTERS
Temperature Rating	194
Trade Name	HYSTACK™
Type	Standard Barrel, Tin Plated
UPC	781810269176
UPC 14 Digit GTIN	00781810269176

Dimensions

Dimension - Bolt Size fraction	1/2
Dimension - Height inch	1.50 in
Dimension - Height mm	38.1 mm
Dimension - Hole Size fraction	1/2

Dimension - L Length Overall mm	76 mm
Dimension - Length Overall inch	3.00 in
Dimension - Stud Size fraction	1/2
Dimension - Stud Size inch	1/2
Dimension - Width inch	1.13 in
Dimension - Width mm	29 mm
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Voltage - Maximum	35000
-------------------	-------

Conductor Related

Conductor - AL Str Size	1000 KCMIL
Conductor - Copper Str Compact Size	1000 KCMIL
Conductor - Copper Str Size	1000 KCMIL
Conductor - Copper Str Size Range	10 AWG - 750 kcmil
Conductor - Material	COPPER
Conductor Type	CODE/FLEX
Wire Size	1000 KCMIL

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	1
Minimum Pack Quantity	1

Product Assets

[3D Models - CUSA442NTC_MODEL-PDF](#)
[3D Models - CUSA442NTC_MODEL-IGES](#)
[3D Models - CUSA442NTC_MODEL-STEP](#)
[Catalogs - BURNDY Master Catalog - Section C - Compression Connections](#)

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Sales Drawings - SC212660-01](#)
[Specifications - CUSA442NTC](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
BRDY-CUSA442NTC-SPEC-EN | REV 7/2025