



## ES2W4W, Insulated AL Service Entrance Compression Sleeve

By Burndy

Catalog # [ES2W4W](#)

Insulated AL service entrance compression sleeve



## Features

- Pre-insulated service entrance compression connector
- Polyethylene caps prevent dirt from accumulating in barrel, grip cable for easy two-hand installation, seal out moisture
- Connector is anchored to jacket assuring the connector is under the die when crimping
- Prefilled with joint compound and stripsealed to limit oxidation and increase life of the connection

## Application

For Insulated Combinations Of Copper, Aluminum, ACSR Compressed Conductors And In Overhead Distribution

## Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Buy America(n) Qualified Certification - ETL	No
Standards - RoHS Compliance Status	Contact Manufacturer
Certification - CSA Approved	CM
UL Listed	No

## Conductor

Conductor - ACSR Str Size A	4 (6/1) Swan AWG;4 (7/1) Swanate AWG
Conductor - ACSR Str Size A Range	4 (6/1) Swan AWG-4 (7/1) Swanate AWG
Conductor - ACSR Str Size B	6 (6/1) Turkey AWG
Conductor - ACSR Str Size B Range	6 (6/1) Turkey AWG
Conductor - AL Str Size A	4 AWG;3 AWG
Conductor - AL Str Size A Range	4 AWG-3 AWG
Conductor - AL Str Size B	6 AWG;5 AWG
Conductor - AL Str Size B Range	6 AWG-5 AWG
Conductor - Copper Solid Size A	2 AWG
Conductor - Copper Solid Size A Range	2 AWG

Conductor - Copper Solid Size B	4 AWG
Conductor - Copper Solid Size B Range	2 AWG
Conductor - Copper Str Size A	4 AWG;3 AWG
Conductor - Copper Str Size A Range	4 AWG-3 AWG
Conductor - Copper Str Size B	6 AWG;5 AWG
Conductor - Copper Str Size B Range	6 AWG-5 AWG

## Dimensions

Dimension - Outside Diameter	.75 in
Dimension - L Length Overall	70 mm
Dimension - Length Overall	2.75 in

## General

Die Index	BG or 5/8
Insulation Type	Nylon
Trade Name	INSULINK™
Insulation	Y
Prefilled Oxide Inhibitor	Y
Sub Brand	INSULINK
Plated	Y
Type	Insulated Service Entrance Connectors
UPC 12 Digit	781810141953
UPC 14 Digit GTIN	00781810141953
Material	Aluminum
Plating Type	Tin - Hot Dipped
UPC	781810141953
Color Code - Side A	Orange
Color Code - Side B	Blue

## Logistics

Minimum Pack Quantity	100
Carton Quantity	100
Pallet Quantity	24000

## Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved  
BRDY-ES2W4W-SPEC-EN | REV 11/2025