

## ES8W8W, Insulated Aluminum Service Entrance Compression Sleeve

By Burndy  
Catalog # [ES8W8W](#)



Insulated AL service entrance compression sleeve

### Features

- Pre-insulated service entrance compression connector
- Polyethylene caps prevent dirt from accumulating in barrel, grip cable for easy two-hand installation, seal out moisture
- Connector is anchored to jacket assuring the connector is under the die when crimping
- Prefilled with joint compound and stripsealed to limit oxidation and increase life of the connection

### Application

For Insulated Combinations Of Copper, Aluminum, ACSR Compressed Conductors And In Overhead Distribution

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

### Conductor

Conductor - AL Str Size A Range	10 AWG-8 AWG
Conductor - AL Str Size B Range	10 AWG-8 AWG
Conductor - Copper Solid Size A	8 AWG
Conductor - Copper Solid Size A Range	8 AWG
Conductor - Copper Solid Size B	8 AWG
Conductor - Copper Solid Size B Range	8 AWG

Conductor - Copper Str Size A Range 10 AWG-8 AWG

Conductor - Copper Str Size B Range 10 AWG-8 AWG

### Dimensions

Dimension - Outside Diameter inch	.75 in
Dimension - L Length Overall mm	70 mm
Dimension - Length Overall inch	2.75 in

### General

Die Index	BG or 5/8
Insulation Type	Nylon
Trade Name	INSULINK™
Insulation	Y
Prefilled Oxide Inhibitor	Y
Sub Brand	INSULINK
Plated	Y
Type	Insulated Service Entrance Connectors
UPC 12 Digit	781810144060
UPC 14 Digit GTIN	00781810144060
Material	Aluminum
Plating Type	Tin - Hot Dipped
UPC	781810144060
Color Code - Side A	Brown
Color Code - Side B	Brown

### Logistics

Minimum Pack Quantity	100
Carton Quantity	100
Pallet Quantity	24000

### Product Assets

[Catalog \[English\]](#)