




## GAR1626, Mechanical Grounding Connector, Cable to Rod or Pipe

By Burndy

Catalog # [GAR1626](#)

Mechanical Grounding Connector, Cable to Rod or Pipe, 4 AWG (Sol)-2/0 AWG (Str), 1-1/4" Pipe, 1-3/8"-1-1/2" Rod, #11 Rebar, Bright Dipped



## Features

- Parallel or 90° Copper Cable Connection
- One-wrench installation
- Rated for Direct Burial in earth or concrete

## Application

For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Direct Burial Cable, Fence Post

## Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL467
	BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

## Conductor

Conductor - Pipe or Round Tube Size Range	1-1/4 in
Conductor - Rebar Size	11
Conductor - Rebar Size Range	11
Conductor - Rod Size	1.380-1.66 in
Conductor - Copper Str Size	2/0 AWG
Conductor - Rod Size Range	1 3/8 in-1 1/2 in
Conductor - Copper Solid Size	4 AWG
Conductor - Copper Solid Size Range	4 AWG-3/0 AWG
Conductor - Copper Str Size Range	5 AWG - 2/0 AWG
Conductor Type	CU C Solid-Size;CU C Str-Size;CU Tube Std-Size;Rod-Size
Conductor - Copper Tube Std Size	1/4 IPS IPS

Conductor - Copper Tube Std Size Range 1/4 IPS IPS

## Dimensions

Dimension - Outside Diameter inch	1.66 in
Dimension - L Length Overall mm	40 mm
Dimension - Height fraction	3-1/2 in
Dimension - Height inch	3.50 in
Dimension - Height mm	88.9 mm
Dimension - Width fraction	3 in
Dimension - Width inch	3.00 in
Dimension - Width mm	76 mm
Dimension - B Length inch	1.88 in
Dimension - Length Overall inch	1.56 in

## Force Related

Installation Torque Recommended in-lb	240 LBS/in
Installation Torque Recommended Run in-lb	240 Lb in

## General

Material - Hardware	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Type	GAR
U Bolt Type	204
UPC 12 Digit	781810233405
UPC 14 Digit GTIN	00781810233405
Material	Copper
Plating Type	Bright Dipped
UPC	781810233405

## Logistics

Minimum Pack Quantity	1
Carton Quantity	30
Pallet Quantity	1500

## Product Assets

[Catalog \[English\]](#)



A Hubbell brand