


## GBM26, Mechanical Grounding Connector, Cable to Bar

By Burndy  
Catalog # [GBM26](#)

Mechanical Grounding Connector, Cable to 1/4" Thick Bar, 4 AWG (Sol)-2/0 AWG (Str), 3/8" Stud.



### Features

- High copper alloy ground connector for joining a range of cable to 1/4" thick bar
- Type GBM clamps cable directly on bar surface
- One-wrench installation
- UL467 Listed
- Suitable for Direct Burial in earth or concrete

### Application

For Copper Cable To Bar, Direct Burial Cable

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Copper Str Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Solid Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - Copper Solid Size Range	#4 AWG-2/0 AWG
Conductor - Copper Str Size Range	4 AWG - 2/0 AWG

### Dimensions

Dimension - L Length Overall mm	24 mm
Dimension - Height inch	1.49 in
Dimension - Height mm	38 mm
Dimension - Width fraction	1-1/3 in
Dimension - Width inch	1.34 in
Dimension - Width mm	34 mm
Dimension - Length Overall inch	0.94 in

### Force Related

Installation Torque Recommended in-lb	240 lb-in
---------------------------------------	-----------

### General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Type	GBM
UPC 12 Digit	781810231449
UPC 14 Digit GTIN	00781810231449
Material	Copper Alloy
Plating Type	Unplated
UPC	781810231449

### Logistics

Minimum Pack Quantity	1
Carton Quantity	125
Pallet Quantity	8500

### Product Assets

[Catalog \[English\]](#)