


GBM34, Mechanical Grounding Connector, Cable to Bar

By Burndy
Catalog # [GBM34](#)



Mechanical Grounding Connector, Cable to 1/4" Thick Bar, 300 kcmil - 500 kcmil, 1/2" Stud

Features

- High copper alloy ground connector for joining a range of cable to 1/4" thick bar
- Type GBM clamps cable directly on bar surface
- One-wrench installation
- UL467 Listed
- Suitable for Direct Burial in earth or concrete

Application

For Copper Cable To Bar, Direct Burial Cable

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Solid Size Range	300 KCMIL - 500 KCMIL
Conductor - Copper Str Size Range	300 kcmil - 500 kcmil

Dimensions

Dimension - L Length Overall mm	35 mm
Dimension - Height inch	2.32 in
Dimension - Height mm	58.9 mm
Dimension - Width fraction	2-2/9 in
Dimension - Width inch	2.22 in
Dimension - Width mm	56 mm
Dimension - Length Overall inch	1.38 in

Force Related

Installation Torque Recommended in-lb	480 lb-in
---------------------------------------	-----------

General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Type	GBM
UPC 12 Digit	781810231463
UPC 14 Digit GTIN	00781810231463
Material	Copper Alloy
Plating Type	Unplated
UPC	781810231463

Logistics

Minimum Pack Quantity	1
Carton Quantity	12

Product Assets

[Catalog \[English\]](#)