


# GC15A, Mechanical Grounding Connector, Cable to Water Pipe, #14-1/0 AWG, 1/2"-1" Pipe, Al/Cu Rated

By Burndy  
Catalog # [GC15A](#)



Mechanical Ground Connector; Cable to Water Pipe

## Features

- Dual-rated for both copper and aluminum conductors providing maximum flexibility
- Tin-plated to provide contact resistance and prevent galvanic corrosion
- Clamps are range taking, only 3 catalog numbers cover the complete range of applications from 1/2 to 4 inches
- UL467 Listed

## Application

For Use With Either Copper Or Aluminum Conductors To Copper Water Pipe, Galvanized Pipe Or Steel Conduit

## Specifications

Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Yes
Industry Standard(s)	UL467
Buy America(n) Qualified	BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
UL Listed	Yes
Certification - UL Listed Direct Burial	No

## Conductor

Conductor - Pipe or Round Tube Run	<ul style="list-style-type: none"> <li>• 1/2</li> <li>• 3/4</li> <li>• 1</li> </ul>
Conductor - Pipe or Round Tube Run Range	1/2 -1
Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 14 AWG</li> <li>• 12 AWG</li> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>

Conductor - AL Str Size	<ul style="list-style-type: none"> <li>• 1 AWG</li> <li>• 1/0</li> <li>• 8 AWG</li> <li>• 6 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> <li>• 2/0 AWG</li> <li>• 3/0 AWG</li> <li>• 4/0 AWG</li> </ul>
Conductor - AL Str Size Range	8 AWG-4/0 AWG
Conductor - Copper Solid Size	<ul style="list-style-type: none"> <li>• 14 AWG</li> <li>• 13 AWG</li> <li>• 12 AWG</li> <li>• 11 AWG</li> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0 AWG</li> </ul>
Conductor - Copper Solid Size Range	14 AWG-1/0 AWG
Conductor - Copper Str Size Range	14 AWG - 1/0 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Solid-Size</li> <li>• CU C Str-Size</li> <li>• Pipe or Tube Round-Run</li> </ul>

## Current

Voltage - Maximum	600 V
-------------------	-------

## Dimensions

Dimension - L Length Overall mm	57 mm
Dimension - Pad Width inch	0.69 in
Dimension - Height mm	0 mm
Dimension - Hole Size inch	0.40 in

Dimension - Hole Size mm 10 mm  
Dimension - Width fraction 11/16 in  
Dimension - Width inch 0.69 in  
Dimension - Width mm 18 mm  
Dimension - Length Overall inch 2.25 in

### Force Related

Installation Torque 180 LBS/in  
Recommended in-lb

### General

Material Type - Screw Steel  
Sub Brand MECHANICAL CONNECTOR  
Physical Attribute - Screw Type Slot  
Plated Y  
Type GC-A, Dual Rated

UPC 12 Digit 781810240007  
UPC 14 Digit GTIN 00781810240007  
Material Aluminum  
Plating Type Tin  
UPC 781810240007

### Logistics

Minimum Pack Quantity 1  
Carton Quantity 250  
Pallet Quantity 6000

### Operational

Temperature Rating -0.4

### Product Assets

[Catalog \[English\]](#)



A Hubbell brand