

## GD1926, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy  
Catalog # [GD1926](#)

Mechanical Grounding Connector, 2 Parallel Cables to Rod or Pipe, 4 AWG (Sol.) - 2/0 AWG (Str.), 2-1/2" Rod, 2-1/2" Pipe.



### Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

### Application

For Joining A Range Of Two Parallel Copper Cables To Rod Or Pipe And Burial In Ground Or Concrete

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Rod Size	2 1/2 in
Conductor - Copper Str Size	4;3;2;1;1/0;2/0
Conductor - Rod Size Range	2 1/2 in
Conductor - Copper Solid Size	4;3;2;1;1/0;2/0
Conductor - Copper Solid Size Range	4-2/0
Conductor - Copper Str Size B Range	2.5
Conductor - Copper Str Size Range	4 AWG - 2/0 AWG

Conductor - Copper Tube Std Size	2-1/2
Conductor - Copper Tube Std Size Range	2-1/2

### Dimensions

Dimension - Height fraction	5 in
Dimension - Height inch	5.00 in
Dimension - Height mm	127 mm
Dimension - Width fraction	4-1/4 in
Dimension - Width inch	4.19 in
Dimension - Width mm	106 mm
Dimension - B Length inch	1.38 in

### Force Related

Installation Torque Recommended in-lb	240 LBS/in
---------------------------------------	------------

### General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Type	GD
U Bolt Type	266
UPC 12 Digit	781810260364
UPC 14 Digit GTIN	00781810260364
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC	781810260364

### Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	1200

### Product Assets

[Catalog \[English\]](#)