

## GD2129, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy  
Catalog # [GD2129](#)



Mechanical Grounding Connector, 2 Parallel Cables to Rod or Pipe, 2/0 AWG (Sol.) - 250 kcmil, 3-1/2" to 4" Rod, 3-1/2" Pipe

### Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

### Application

For Joining A Range Of Two Parallel Copper Cables To Rod Or Pipe And Burial In Ground Or Concrete

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Industry Standard(s)	UL467
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes
Buy America(n) Qualified	Contact Manufacturer

### Conductor

Conductor - Copper Solid Size	2/0;3/0;4/0
Conductor - Copper Solid Size Range	2/0-4/0
Conductor Size	2/0 AWG Sol - 250 kcmil
Conductor - Copper Str Size B Range	3.5
Conductor - Copper Str Size	2/0;3/0;4/0;250
Conductor - Copper Str Size Range	2/0 AWG - 250 kcmil

Conductor - Copper Tube Std Size	3-1/2
Conductor - Copper Tube Std Size Range	3-1/2

### Dimensions

Dimension - Width inch	5.31 in
Dimension - Width mm	135 mm
Dimension - B Length inch	1.50 in
Dimension - Height fraction	6-1/4 in
Dimension - Height inch	6.25 in
Dimension - Height mm	158.8 mm
Dimension - Width fraction	5-3/8 in

### Force Related

Installation Torque Recommended in-lb	240 LBS/in
---------------------------------------	------------

### General

Sub Brand	MECHANICAL CONNECTOR
Plated	N
Material Type - Screw Type	DURIUM™ Silicon Bronze GD
U Bolt Type	264
UPC 12 Digit	781810260432
UPC 14 Digit GTIN	00781810260432
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC	781810260432

### Logistics

Minimum Pack Quantity	1
-----------------------	---

### Product Assets

[Catalog \[English\]](#)