

GG171, Mechanical Grounding Connector, Copper Bar, Strap, Braid, or Cable to Rod or Tube

By Burndy
Catalog # GG171



Mechanical Grounding Connector, Copper Bar, Strap, Braid or Cable to Rod or Tube, 1-1/2" Pipe, 1-5/8" - 1-7/8" Rod

Features

- High copper alloy ground connector for joining bar, strap, braid or cable to rod or tube
- Rated for Direct Burial in earth or concrete
- UL467 Listed
- One wrench installation
- Type GG connector is particularly effective for use with braid for ground rods, switch handles, fence posts and gates

Application

For Joining Copper Bar, Strap, Braid Or Cable To Rod Or Tube, Direct Burial Cables

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Tube Std Size 1-5/8;1-3/4;1-7/8

Dimensions

Dimension - Height fraction	3-1/2 in
Dimension - Height mm	88.9 mm
Dimension - Width inch	3.25 in
Dimension - Width mm	83 mm
Dimension - B Length inch	1.38 in

Force Related

Installation Torque Recommended in-lb	240 LBS/in
---------------------------------------	------------

General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Type	GG
U Bolt Type	199
UPC 12 Digit	781810990049
UPC 14 Digit GTIN	00781810990049
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC	781810990049

Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	2160

Product Assets

[Catalog \[English\]](#)