

# GG1925, Mechanical Grounding Connector, Copper Bar, Strap, Braid, or Cable to Rod or Tube

By Burndy  
Catalog # [GG1925](#)



Mechanical Grounding Connector, Copper Bar, Strap, Braid or Cable to Rod or Tube, 2-1/2" Pipe, 2-1/2"-2 7/8" Rod

## Features

- High copper alloy ground connector for joining bar, strap, braid or cable to rod or tube
- Rated for Direct Burial in earth or concrete
- UL467 Listed
- One wrench installation
- Type GG connector is particularly effective for use with braid for ground rods, switch handles, fence posts and gates

## Application

For Joining Copper Bar, Strap, Braid Or Cable To Rod Or Tube, Direct Burial Cables

## Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No
Certification - UL Listed Direct Burial	Yes

## Dimensions

Dimension - Height mm	127 mm
Dimension - Width inch	4.56 in
Dimension - Width mm	116 mm
Dimension - B Length inch	1.88 in

## Force Related

Installation Torque Recommended in-lb	480 LBS/in
---------------------------------------	------------

## General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Type	GG
U Bolt Type	232
UPC 12 Digit	781810260098
UPC 14 Digit GTIN	00781810260098
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC	781810260098

## Logistics

Minimum Pack Quantity	1
Carton Quantity	1
Pallet Quantity	1

## Product Assets

[Catalog \[English\]](#)