

## GK1429, Copper Alloy Grounding Clamp, 3 Cables to Rod or Pipe

By Burndy  
Catalog # [GK1429](#)



Mechanical Grounding Connector, 3 Cables to Rod or Pipe, 2/0 AWG (Sol.) - 250 kcmil, 1/2" - 3/4" Pipe, 7/8" - 1" Rod, 1/2" Stud

### Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

### Application

For Joining Three Equal Copper Cables To Rod Or Tube, Direct Burial In Earth Or Concrete

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Rod Size	7/8 in;1 in
Conductor - Rod Size Range	7/8 in-1 in
Conductor Size	2/0 AWG Sol - 250 kcmil

### Dimensions

Dimension - Height inch	3.69 in
Dimension - Height mm	93.7 mm
Bolt Size	1/2 in
Dimension - Width fraction	3-7/8 in
Dimension - Width inch	3.81 in
Dimension - Width mm	97 mm
Dimension - B Length inch	1.63 in

### Force Related

Installation Torque Recommended in-lb	480 LBS/in
---------------------------------------	------------

### General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Type	Three Cables to Rod or Tube
UPC 12 Digit	781810233566
UPC 14 Digit GTIN	00781810233566
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC	781810233566

### Logistics

Minimum Pack Quantity	1
Carton Quantity	6
Pallet Quantity	864

### Product Assets

[Catalog \[English\]](#)