


GK6429, Copper Alloy Grounding Clamp, 3 Cables to Rod or Pipe

By Burndy
Catalog # [GK6429](#)



Mechanical Grounding Connector, 3 Cables to Rod or Pipe, 2/0 AWG (Sol) -250 kcmil, 3/8" Pipe, 5/8"-3/4" Rod

Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

Application

For Joining Three Equal Copper Cables To Rod Or Tube, Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rod Size	5/8 in ; 3/4 in
Conductor Size	2/0 AWG Sol - 250 kcmil

Dimensions

Dimension - Height inch	2.88 in
Dimension - Height mm	73.2 mm
Bolt Size	1/2 in
Dimension - Width fraction	3-1/2 in
Dimension - Width inch	3.50 in
Dimension - Width mm	89 mm
Dimension - B Length inch	1.63 in

Force Related

Installation Torque	480 LBS/in
Recommended in-lb	

General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Type	Three Cables to Rod or Tube
UPC 12 Digit	781810233535
UPC 14 Digit GTIN	00781810233535
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC	781810233535

Logistics

Minimum Pack Quantity	1
Carton Quantity	6
Pallet Quantity	864

Product Assets

[Catalog \[English\]](#)