

GK644C, Copper Alloy Grounding Clamp, 3 Cables to Rod or Pipe

By Burndy
Catalog # [GK644C](#)



Mechanical Grounding Connector, 3 Cables to Rod or Pipe, 8 AWG (Sol.) - 4/0 AWG (Str.), 3/8" Pipe, 5/8" - 3/4" Rod, 3/8" Stud

Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

Application

For Joining Three Equal Copper Cables To Rod Or Tube, Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL467
Certification - ETL	Contact Manufacturer
Standards - Industry Standards Met	No
Standards - RoHS Compliance Status	UL467
Certification - CSA Approved	EX
UL Listed	No
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rod Size	5/8 in ; 3/4 in
Conductor Size	#8 AWG Sol - 4/0 AWG Str

Dimensions

Dimension - Height inch	2.81 in
Dimension - Height mm	71.4 mm
Bolt Size	3/8 in
Dimension - Width fraction	2-5/8 in
Dimension - Width inch	2.63 in
Dimension - Width mm	67 mm
Dimension - B Length inch	1.38 in

Force Related

Installation Torque	240 LBS/in
Recommended in-lb	

General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Type	Three Cables to Rod or Tube
UPC 12 Digit	781810233511
UPC 14 Digit GTIN	00781810233511
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC	781810233511

Logistics

Minimum Pack Quantity	1
Carton Quantity	1
Pallet Quantity	1

Product Assets

[Catalog \[English\]](#)