



GP644C, Mechanical Grounding Connector, 2 Cables to Rod or Pipe

By Burndy
Catalog # [GP644C](#)

Mechanical Grounding Connector, 2 Cables to Rod or Pipe, 8 AWG (Sol.) - 4 AWG (Str.), 3/8" Pipe, 5/8" - 3/4" Rod, 3/8" Stud



Features

- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets
- One-wrench installation

Application

For Joining A Range Of Parallel Copper Cables Perpendicular To Rod, Pipe Or Column, Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rod Size	5/8 in;3/4 in
Conductor - Copper Str Size	9;8;7;6;5;4
Conductor - Rod Size Range	5/8 in-3/4 in
Conductor - Copper Solid Size	8;7;6;5;4;3
Conductor - Copper Solid Size Range	8-3
Conductor - Copper Str Size B Range	0.375
Conductor - Copper Str Size Range	9-4
Conductor - Copper Tube Std Size	5/8;3/4

Conductor - Copper Tube Std Size Range 5/8-3/4

Dimensions

Dimension - L Length Overall mm	33 mm
Dimension - Height fraction	2-1/2 in
Dimension - Height inch	2.50 in
Dimension - Height mm	63.5 mm
Dimension - Width fraction	2-1/8 in
Dimension - Width inch	2.12 in
Dimension - Width mm	54 mm
Dimension - B Length inch	1.50 in
Dimension - Length Overall inch	1.31 in

Force Related

Installation Torque Recommended in-lb	240 LBS/in
---------------------------------------	------------

General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Type	GP
U Bolt Type	187
UPC 12 Digit	781810260531
UPC 14 Digit GTIN	00781810260531
Material	Copper Alloy
Plating Type	Unplated
UPC	781810260531

Logistics

Minimum Pack Quantity	10
Carton Quantity	1
Pallet Quantity	1

Product Assets

[Catalog \[English\]](#)