

## GRF4C3, Universal Grounding Clamp, 1 or 2 Conductors to Round or Square Pedestal

By Burndy  
Catalog # [GRF4C3](#)

Universal Grounding Clamp, 1 or 2 Nos of Conductors, 8 AWG-2 AWG, Pedestal Type : 1" (Round), Upto 7/8" (Square), 3/8" Stud



### Features

- One connector fits all applications
- Ease of specification and installation
- Single bolt design with no need to disassemble
- Single wrench installation
- Accepts 1 or 2 ground conductors
- Requires less connectors to install signal reference grid
- Tin plated cast bronze construction
- Resists corrosion and provides extended life ground connection
- Grounds all pedestals (round or square)
- Will accept up to 7/8" Square and up to 1" Round
- Serves 3 needs: Signal Reference Grid, Static Ground, Fault Current Ground
- UNIGROUND™ connector will solve all ground problems found in computer applications today
- UL467 Listed for the US and Canadian Markets

### Application

For Raised Floor Systems

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	No

### Conductor

Conductor - Pipe or Round Tube Size	<ul style="list-style-type: none"> <li>• 3/8</li> <li>• 1/2</li> <li>• 3/4</li> <li>• 1</li> </ul>
Conductor - Pipe or Round Tube Size Range	3/8 in -1 in

Conductor - Pipe or Square Tube Size	<ul style="list-style-type: none"> <li>• 1/2</li> <li>• 5/8</li> <li>• 3/4</li> <li>• 7/8</li> </ul>
Conductor - Pipe or Square Tube Size Range	1/2 in -7/8 in
Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>
Conductor - Copper Solid Size	<ul style="list-style-type: none"> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>
Conductor - Copper Solid Size Range	8 AWG-2 AWG
Number Of Conductors	<ul style="list-style-type: none"> <li>• 1</li> <li>• 2</li> </ul>
Conductor - Copper Str Size Range	8 AWG-2 AWG

### Dimensions

Dimension - Height inch	3.14 in
Dimension - Height mm	79.8 mm
Dimension - Width inch	1.76 in
Dimension - Width mm	45 mm
Dimension - B Length inch	1.96 in

### Force Related

Installation Torque Recommended in-lb	100 LBS/in
---------------------------------------	------------

### General

Material - Hardware Trade Name	DURIUM™ Silicon Bronze
Sub Brand	UNIGROUND™
Pedestal Type	<ul style="list-style-type: none"> <li>• Round</li> <li>• Square</li> </ul>
Plated Type	Y GRF

UPC 12 Digit	781810828021
UPC 14 Digit GTIN	00781810828021
Material	Copper Alloy
Plating Type	Tin - Electro Plated
UPC	781810828021

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	2800

### Product Assets

[Catalog \[English\]](#)

---

### Logistics



A Hubbell brand