

GSTUD14HY Structural Steel Ground Stud

By Burndy

Catalog # [GSTUD14HY](#)

Structural Steel Grounding Connector



Features

- May be welded to steel surfaces quickly and easily
- No disk grinding needed
- Knurled surface for better gripping
- Copper plated
- May be installed during adverse weather conditions

Application

For Compression Connectors And Mechanical Connectors

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
Certification - CSA Approved	No
UL Listed	No
Certification - UL Listed Direct	No
Burial	

Conductor

Conductor - Rod Size	1/4 in
Conductor - Copper Str Size	6 AWG
Conductor - Rod Size Range	1/4 in
Conductor - Copper Str Size Range	6 AWG
Conductor Type	Rod-Size;CU C Str-Size

Dimensions

Dimension - L Length Overall	122 mm
mm	
Dimension - Ground Rod Size	1/4 in
Dimension - Height mm	0 mm
Dimension - B Length fraction	13/50 in
Dimension - B Length inch	0.26 in
Physical Attribute - Tongue	45 Degree
Angle	
Dimension - Length Overall	4.81 in
inch	
Dimension - D inch	1.25 in

General

Trade Name	VERSITAIL™
Sub Brand	HYGROUND, VERSITAIL
Plated	Y
Type	GSTUD-HY
UPC 12 Digit	781810220870
UPC 14 Digit GTIN	00781810220870
Material	Steel
Plating Type	Nickel
UPC	781810220870

Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	9600

Product Assets

[Catalog \[English\]](#)