



HSB110H48PF5, Cross-Linked Polyolefin Heat Shrinkable Heavy Wall Tube, 1 - 3/0 AWG, 1500 V, Shrink Ratio: 3 : 1.

By Burndy
Catalog # [HSB110H48PF5](#)

Thick wall heat shrink tubing



Features

- Heavy Wall Heat Shrink Tubing
- Shrink Ratio 3:1
- Inside diameter is coated with adhesive sealant to protect against moisture and corrosion
- Rated to 1500V
- UL486D Listed for Direct Burial

Application

For Direct Burial

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor Size	1AWG - 3/0AWG
Conductor Range	#1 AWG to #3/0 AWG

Configuration

Connector Type HEAVY WALL TUBES

Current

Voltage Rating 1500 V

Dimensions

Package Length	50 in
Package Width	4 in
Package Weight	28 lb.
Package Height	4 in

General

Sub Brand	HEAT SHRINK
Type	HS-H-PF, Heavy Wall, Flame Retardant
Material	Cross-linked Polyolefin
UPC	781810214909

Logistics

Minimum Pack Quantity	1
Number of Pieces in Package	5
Carton Quantity	5
Pallet Quantity	36

Product Assets

[Catalog \[English\]](#)