



HSB12T48PF, Heat Shrink Tubing, 0.50" ID Min.(Exp.), 0.25" ID Max. (Rec.), Polyolefin, Thin Wall, Black, Shrink ratio-2:1, 600V, 4 Ft Reel.



By Burndy
Catalog # [HSB12T48PF](#)

Heat Shrink Tubing, 0.50" ID Min.(Exp.), 0.25" ID Max.(Rec.), Polyolefin, Thin Wall, Black, Shrink ratio-2:1, 600V, 4 Ft Reel.

General

Catalog Number HSB12T48PF
Connector Type THIN WALL REEL
Material Cross-linked Polyolefin
UPC 781810212714

Conductor Related

Conductor Range #6 AWG to #2 AWG
Conductor Size 6AWG - 2AWG

Certifications And Compliance

Certification - ETL No
Standards - RoHS Compliance CM
Status

UL Listed No

Logistics

Minimum Pack Quantity 1

Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide](#)
- [Product Cross Section Image\(s\) - BUR_HSB38T300PF_LineArt](#)
- [Sales Drawings - SD211941](#)
- [Specifications - HSB12T48PF](#)