

DRAWING NO.		4		3		2		1	
SPEC 834-01									
CATALOG NUMBER	QTY OF PIECES PER KIT	I.D. EXPANDED		I.D. AFTER RECOVERY		WALL THICKNESS		CONDUCTOR RANGE	STANDARD PIECE LENGTH (IN.)
		IN.	mm	IN.	mm	IN.	mm		
HSB35H3PF25	25	.35	8.9	.12	3	.07	1.8	#14-10	3
HSB35H6PF25	25	.35	8.9	.12	3	.07	1.8	#14-10	6
HSB35H48PF5	5	.35	8.9	.12	3	.07	1.8	#14-10	4.8
HSB34H2PF25	25	.75	19.1	.24	6.1	.09	2.3	#6-2	2
HSB34H4PF25	25	.75	19.1	.24	6.1	.09	2.3	#6-2	4
HSB34H6PF10	10	.75	19.1	.22	5.6	.09	2.3	#6-2	6
HSB34H9PF10	10	.75	19.1	.22	5.6	.09	2.3	#6-2	9
HSB34H48PF5	5	.75	19.1	.22	5.6	.09	2.3	#6-2	4.8
HSB110H2PF25	25	1.10	27.9	.35	8.9	.12	3.0	#1-3/0	2
HSB110H4PF25	25	1.10	27.9	.35	8.9	.12	3.0	#1-3/0	4
HSB110H6PF5	5	1.10	27.9	.40	10.2	.12	3.0	#1-3/0	6
HSB110H9PF5	5	1.10	27.9	.40	10.2	.12	3.0	#1-3/0	9
HSB110H48PF5	5	1.10	27.9	.40	10.2	.12	3.0	#1-3/0	4.8
HSB150H4PF25	25	1.50	38.1	.47	11.9	.16	4.1	2/0-350	4
HSB150H9PF3	3	1.50	38.1	.50	12.7	.16	4.1	2/0-350	9
HSB150H12PF3	3	1.50	38.1	.50	12.7	.16	4.1	2/0-350	12
HSB150H48PF5	5	1.50	38.1	.50	12.7	.16	4.1	2/0-350	4.8
HSB200H9PF2	2	2.00	50.8	.63	16	.16	4.1	250-500	9
HSB200H12PF2	2	2.00	50.8	.63	16	.16	4.1	250-500	12
HSB200H48PF2	2	2.00	50.8	.63	16	.16	4.1	250-500	4.8
HSB270H18PFM0<2	1	2.70	68.1	.87	22.1	.15	3.8	600-1000	18
HSB354H300PF	1	3.54	89.9	1.18	30	.15	3.8	--	300

NOTES:

1. MATERIAL: HEAVY WALL POLYOLEFIN HEAT SHRINK TUBING.
2. THE CATALOG SUFFIX "-M0" INDICATES NO ADHESIVE ON THE I.D.
ALL OTHER HEAVY WALL HEAT SHRINK SLEEVES LISTED EITHER HAVE A HOT MELT ADHESIVE OR MASTIC ON THE I.D. FOR SEALING PURPOSES.
3. ALL SEMI-RIGID HEAT SHRINK SLEEVES ARE UL RECOGNIZED AND CSA CERTIFIED.
4. CONTINUOUS OPERATING TEMPERATURE: -55°C TO 110°C
5. SHRINK TEMPERATURE: 120°C
6. 3:1 SHRINK RATIO.
7. RATED VOLTAGE: 600V
8. SHRINK INSTRUCTIONS:

A) THE ARTICLE TO BE COVERED MUST BE CLEAN AND DRY.
B) INSERT THE ARTICLE TO BE COVERED INTO TUBING.
C) APPLY HEAT TO THE TUBING WITH A BACK AND FORTH MOTION FROM END TO END.
D) REMOVE HEAT AS SOON AS THE TUBING BEGINS TO ASSUME THE SHAPE OF THE ARTICLE.
9. PREFIX "HSR" DENOTES RED TUBING.

REV.	DATE	DESCRIPTION	ECO	BY	CHK'D
F	12/07/15	FOCUS REQUEST FRUSTING42	42340	KM	MB

HEAVY WALL HEAT SHRINK	
ITEM NO. N/A	
CAT. NO. HSB- -H- -PF- (TABLE)	
SCALE 1/4"	DATE 6/26/25
DRAWN BY: J. BOSTER	DESIGNED BY: J. BOSTER
CHK'D BY: J. BOSTER	DATE: 6/26/25
REV. A	REV. 1
DATE: 6/26/25	DATE: 6/26/25
PROJECT NO. SD211942-01	PROJECT NO. SD211942-01
SHEET 1 OF 1	REV. F

TO ORDER BURNDY® PRODUCTS CALL

UNITED STATES:
1-800-346-4175 (LONDONDERRY, NH)

CANADA:
1-800-361-6975 (QUEBEC)

1-800-387-6487 (ALL OTHER PROVINCES)

FOR PRODUCT INFO: <http://www.burndy.com>