

DRAWING NO. SD211942-01									
CATALOG NUMBER	QTY OF PIECES PER KIT	I.D. EXPANDED		I.D. AFTER RECOVERY		WALL THICKNESS		CONDUCTOR RANGE	STANDARD PIECE LENGTH (IN.)
		IN.	mm	IN.	mm	IN.	mm		
HSB35H3PF25	25	.35	8.9	.12	3	.07	1.8	#14-10	3
HSB35H6PF25	25	.35	8.9	.12	3	.07	1.8	#14-10	6
HSB35H6PF50	50	.35	8.9	.12	3	.07	1.8	#14-10	6
HSB35H48PF5	5	.35	8.9	.12	3	.07	1.8	#14-10	48
HSB34H2PF25	25	.75	19.1	.24	6.1	.09	2.3	#6-2	2
HSB34H4PF25	25	.75	19.1	.24	6.1	.09	2.3	#6-2	4
HSB34H6PF10	10	.75	19.1	.22	5.6	.09	2.3	#6-2	6
HSB34H6PF50	50	.75	19.1	.22	5.6	.09	2.3	#6-2	6
HSB34H9PF10	10	.75	19.1	.22	5.6	.09	2.3	#6-2	9
HSB34H48PF5	5	.75	19.1	.22	5.6	.09	2.3	#6-2	48
HSB110H2PF25	25	1.10	27.9	.35	8.9	.12	3.0	#1-3/0	2
HSB110H4PF25	25	1.10	27.9	.35	8.9	.12	3.0	#1-3/0	4
HSB110H6PF5	5	1.10	27.9	.40	10.2	.12	3.0	#1-3/0	6
HSB110H6PF50	50	1.10	27.9	.40	10.2	.12	3.0	#1-3/0	6
HSB110H9PF5	5	1.10	27.9	.40	10.2	.12	3.0	#1-3/0	9
HSB110H9PF50	50	1.10	27.9	.40	10.2	.12	3.0	#1-3/0	9
HSB110H48PF5	5	1.10	27.9	.40	10.2	.12	3.0	#1-3/0	48
HSB150H4PF25	25	1.50	38.1	.47	11.9	.16	4.1	2/0-350	4
HSB150H9PF3	3	1.50	38.1	.50	12.7	.16	4.1	2/0-350	9
HSB150H9PF51	51	1.50	38.1	.50	12.7	.16	4.1	2/0-350	9
HSB150H12PF3	3	1.50	38.1	.50	12.7	.16	4.1	2/0-350	12
HSB150H48PF5	5	1.50	38.1	.50	12.7	.16	4.1	2/0-350	48
HSB200H9PF2	2	2.00	50.8	.63	16	.16	4.1	250-500	9
HSB200H9PF50	50	2.00	50.8	.63	16	.16	4.1	250-500	9
HSB200H12PF2	2	2.00	50.8	.63	16	.16	4.1	250-500	12
HSB200H12PF50	50	2.00	50.8	.63	16	.16	4.1	250-500	12
HSB200H48PF2	2	2.00	50.8	.63	16	.16	4.1	250-500	48
HSB270H18PFM0	1	2.70	68.1	.87	22.1	.15	3.8	600-1000	18
HSB270H18PF2	2	2.70	68.1	.87	22.1	.15	3.8	600-1000	18
HSB354H300PF	1	3.54	89.9	1.18	30	.15	3.8	--	300

REV.	DATE	DESCRIPTION	ECO	BY	C'K'D.
H	12/11/17	UPDATED AS PER MARKUP	48124	YR	VS

NOTES:

- MATERIAL: HEAVY WALL POLYOLEFIN HEAT SHRINK TUBING.
- THE CATALOG SUFFIX "-M0" INDICATES NO ADHESIVE ON THE I.D.
ALL OTHER HEAVY WALL HEAT SHRINK SLEEVES LISTED EITHER HAVE A HOT MELT ADHESIVE OR MASTIC ON THE I.D. FOR SEALING PURPOSES.
- ALL SEMI-RIGID HEAT SHRINK SLEEVES ARE UL RECOGNIZED AND CSA CERTIFIED.
- CONTINUOUS OPERATING TEMPERATURE: -55°C TO 110°C
- SHRINK TEMPERATURE: 120°C
- 3:1 SHRINK RATIO.
- RATED VOLTAGE: 600V
- SHRINK INSTRUCTIONS:
 - THE ARTICLE TO BE COVERED MUST BE CLEAN AND DRY.
 - INSERT THE ARTICLE TO BE COVERED INTO TUBING.
 - APPLY HEAT TO THE TUBING WITH A BACK AND FORTH MOTION FROM END TO END.
 - REMOVE HEAT AS SOON AS THE TUBING BEGINS TO ASSUME THE SHAPE OF THE ARTICLE.
- PREFIX "HSB" DENOTES BLACK TUBING.

TO ORDER BURNDY® PRODUCTS CALL		HEAVY WALL HEAT SHRINK	
UNITED STATES: 1-800-346-4175 (LONDONDERRY, NH)		ITEM NO: N/A	
CANADA: 1-800-361-6975 (QUEBEC) 1-800-387-6487 (ALL OTHER PROVINCES)		CAT NO: HSB--H--PF- (TABLE)	
FOR PRODUCT INFO: http://www.burndy.com			
		DRAWING NO	
		SD211942-01	
		SHEET 1 of 1	