



HSIC200FR, Heat Shrinkable End Cap, 2" ID Min.(Exp.), 0.63" ID Max. (Rec.), 250-1111 Flex, Heavy Wall, Black



By Burndy
Catalog # [HSIC200FR](#)

Heat Shrinkable End Cap, 2" ID Min.(Exp.), 0.63" ID Max.(Rec.), 250-1111 Flex, Cross Linked Polyolefin, Heavy Wall, Flame Retardant, Black, 600V.

Application

For Used To Insulating Exposed Conductors In Energized Applications

General

Catalog Number	HSIC200FR
Color	Black
EU RoHS Indicator	Yes
Material	Cross-linked Polyolefin
Sub Brand	HEAT SHRINK
Type	HSIC-FR, Heavy Wall, Fire Retardant
UPC	781810266533

Conductor Related

Conductor Range	250-1111 kcmil
-----------------	----------------

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2025)
--------------------------	---

Standards - RoHS Compliance CM
Status

Logistics

Carton Quantity	10
Minimum Pack Quantity	1

Product Assets

- [3D Models - HSIC200FR_MODEL-PDF](#)
- [3D Models - HSIC200FR_MODEL-IGES](#)
- [3D Models - HSIC200FR_MODEL-STEP](#)
- [Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide](#)
- [Product Cross Section Image\(s\) - BUR_HSIC10-500FR_LineArt](#)
- [Sales Drawings - SC209680-01](#)
- [Specifications - HSIC200FR](#)
- [Video - Heat Shrink Product Overview & Installation](#)



A Hubbell brand