




K11A34U2, Two Conductor Two Hole Mounting Stacked Aluminum Panel Board Set Screw Connector

By Burndy
Catalog # [K11A34U2](#)



Aluminum Universal Terminal, 2 Hole, 4/0 AWG-500 kcmil

Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - AL Str Size	4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil
Conductor - AL Str Size Range	4/0 AWG-500 kcmil
Conductor - Copper Solid Size	4/0 AWG
Conductor - Copper Solid Size Range	4/0 AWG
Number Of Conductors	2
Conductor Size	4/0 AWG-500 KCMIL
Conductor - Copper Str Size Range	4/0 AWG-500 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size;CU C Solid-Size

Configuration

Physical Attribute - Number of Holes	2
Connector Type	Stacked

Dimensions

Dimension - L Length Overall mm	74 mm
Dimension - Pad Width inch	1.45 in
Dimension - Height fraction	2.4 in
Dimension - Height inch	2.40 in
Dimension - Height mm	61 mm
Dimension - Hole Size inch	0.28 in
Dimension - Hole Size mm	7 mm
Dimension - Screw Size inch	15/16
Dimension - Stud Size fraction	1/4
Dimension - Stud Size inch	1/4 in
Dimension - Width fraction	1-11/25 in
Dimension - Width inch	1.44 in
Dimension - Width mm	37 mm
Dimension - Bolt Hole Size inch	0.25 in
Dimension - Bolt Size fraction	1/4
Dimension - Length Overall inch	2.91 in
Dimension - D inch	2.31 in
Dimension - N inch	0.25 in

Force Related

Installation Torque Recommended in-lb	375 LBS/in
---------------------------------------	------------

General

Material - Hardware	Aluminum
Sub Brand	UNIVERSAL TERM
Physical Attribute - Screw Type Plated	Allen Y
Type	Bolted Lugs & Terminals
UPC 12 Digit	781810370278
UPC 14 Digit GTIN	00781810370278
Material	Aluminum
Hex Key	3/8
Plating Type	Tin plated
UPC	781810370278

Logistics

Minimum Pack Quantity	1
-----------------------	---

Carton Quantity 90
Pallet Quantity 90

Temperature Rating 194

Product Assets

Operational

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-K11A34U2-SPEC-EN | REV 11/2025