



K2A36U2N, AL Universal Term, 2 Conductor, 2-Hole, #2 AWG Str-600 kcmil, 1/2" Stud, 1.75" Spacing, 2 Screws, Al/Cu Rated

By Burndy

Catalog # [K2A36U2N](#)

Aluminum Universal Terminal, 2 Conductor, 2 Hole, 2 AWG (Str)-600 kcmil



Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	<ul style="list-style-type: none"> • Buy America Compliant (All status valid till December 2025) • Buy American Act Compliant (All status valid till December 2025) • BABA Compliant (All status valid till December 2025)
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil • 500 kcmil • 550 kcmil
-----------------------------	---

Conductor - AL Str Size	<ul style="list-style-type: none"> • 600 kcmil • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil • 500 kcmil • 550 kcmil • 556 kcmil • 600 kcmil
Conductor - AL Str Size Range	2 Str. - 600 Kcmil
Number Of Conductors	2
Conductor Size	2 AWG-600 KCMIL
Conductor - Copper Str Size Range	2 Str. - 600 Kcmil
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size

Configuration

Physical Attribute - Number of Holes	2
Connector Type	Parallel Set-Screw

Dimensions

Dimension - L Length Overall mm	119 mm
Dimension - Pad Width inch	2.42 in
Dimension - Height fraction	1.4 in
Dimension - Height inch	1.39 in
Dimension - Height mm	35.3 mm
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - Screw Size inch	3/8
Dimension - Stud Size inch	1/2 in

Dimension - Width fraction	2-41/100 in
Dimension - Width inch	2.42 in
Dimension - Width mm	61 mm
Dimension - Bolt Hole Size inch	0.50 in
Dimension - Bolt Size fraction	1/2
Dimension - Length Overall inch	4.69 in
Dimension - D inch	3.22 in
Dimension - N inch	0.63 in

Force Related

Installation Torque Recommended in-lb	375 LBS/in
---------------------------------------	------------

General

Material - Hardware	Aluminum
Sub Brand	UNIVERSAL TERM
Physical Attribute - Screw Type	Slot
Plated	N

Type	Bolted Lugs & Terminals
UPC 12 Digit	781810600351
UPC 14 Digit GTIN	00781810600351
Hardware Type	3/8 UNC Slotted Set Screw
Material	Aluminum
Plating Type	Tin plated
UPC	781810600351

Logistics

Minimum Pack Quantity	1
Carton Quantity	54
Pallet Quantity	1728

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand