


## K2C22, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy  
Catalog # [K2C22](#)



SERVIT POST™ Mechanical Connector, 2 Cables to Flat

### Features

- SERVIT POST™ mechanical connector used to ground 1 or 2 cables to steel structures, fence posts, and transformers
- Also used to tap 1 or 2 cables from bus bar
- 1-Wrench installation

### Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> </ul>
Conductor - Copper Solid Size	<ul style="list-style-type: none"> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> </ul>

	• 2 AWG
Conductor - Copper Solid Size Range	2 AWG - 10 AWG
Conductor - Copper Str Size Range	3 AWG - 10 AWG
Physical Attribute - Number of Conductors Accommodated Total	2

### Dimensions

Dimension - Nut Width inch	0.75 in
Dimension - L Length Overall mm	41.1 mm
Dimension - P inch	0.26 in
Dimension - Height fraction	1
Dimension - Height inch	1.25 in
Dimension - Height mm	25.4 mm
Dimension - Threads per inch	16
Dimension - Width inch	32 mm
Dimension - B Length fraction	15/32 in
Dimension - B Length inch	0.46 in
Dimension - Body Width inch	0.62 in
Dimension - Bolt Size fraction	3/8
Dimension - Length Overall inch	1.62 in
Dimension - D inch	0.62 in

### Force Related

Stud Installation Torque inch pounds	280 LBS/in
--------------------------------------	------------

### General

Trade Name	SERVIT POST™
Sub Brand	SERVIT POST
Plated	N
Type	KC and K2C Series
UPC 12 Digit	781810257104
UPC 14 Digit GTIN	00781810257104
Material	Bronze Alloy, Leaded
Plating Type	Unplated
UPC	781810257104

### Logistics

Minimum Pack Quantity	1
Carton Quantity	50

Pallet Quantity

14850

**Product Assets**

[Catalog \[English\]](#)

---



A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved  
BRDY-K2C22-SPEC-EN | REV 1/2026