

## K3A2U2, AL Universal Terminal, 3 Conductor, #14-2 AWG Str, 2-Hole, 5/16" Stud, .88" Spacing, 3 Screws, Al/Cu Rated

By Burndy  
Catalog # [K3A2U2](#)

Aluminum Universal Terminal, 3 Conductor, 14-2 AWG (Str)



### Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

### Application

For Aluminum and Copper Conductors

### Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	<ul style="list-style-type: none"> <li>• Buy American Act Compliant (All status valid till December 2025)</li> <li>• BABA Compliant (All status valid till December 2025)</li> </ul>
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

### Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> <li>• 14 AWG</li> <li>• 12 AWG</li> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>
Conductor - AL Str Size	<ul style="list-style-type: none"> <li>• 8 AWG</li> <li>• 6 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>
Conductor - AL Str Size Range	14-2 AWG
Number Of Conductors	3

Conductor Size	14-2 AWG
Conductor - Copper Str Size Range	14-2 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul>

### Configuration

Physical Attribute - Number of Holes	2
Physical Attribute - Number of Screws	3
Connector Type	Parallel Set-Screw

### Dimensions

Dimension - L Length Overall mm	55.62 mm
Dimension - Pad Width inch	1.64 in
Dimension - Height fraction	5/8 in
Dimension - Height inch	0.62 in
Dimension - Height mm	15.7 mm
Dimension - Hole Size fraction	11/32
Dimension - Hole Size inch	0.34 in
Dimension - Hole Size mm	9 mm
Dimension - Stud Size inch	5/16 in
Dimension - Width fraction	1-59/100 in
Dimension - Width inch	1.64 in
Dimension - Width mm	40 mm
Dimension - Bolt Hole Size inch	0.57 in
Dimension - Bolt Size fraction	5/16
Dimension - Length Overall inch	2.19 in
Dimension - D inch	1.63 in
Dimension - N inch	0.34 in

### Force Related

Installation Torque Recommended in-lb	50 LBS/in
---------------------------------------	-----------

### General

Material - Hardware	Aluminum
Sub Brand	UNIVERSAL TERM
Physical Attribute - Screw Type Plated	Slot Y
Type	Bolted Lugs & Terminals
UPC 12 Digit	781810370360

UPC 14 Digit GTIN 00781810370360  
Material Aluminum  
Plating Type Tin plated  
UPC 781810370360

Pallet Quantity 3240

### Operational

Temperature Rating 194

### Logistics

Minimum Pack Quantity 1  
Carton Quantity 216

### Product Assets

[Catalog \[English\]](#)



A Hubbell brand