



**KA25, Cu Set Screw Lug Connector, 1-Hole,
#4-1/0 AWG Str, 3/8" Stud, 1 Screw**

By Burndy
Catalog # [KA25](#)

Copper Terminal, 1 Hole, 4-1/0 AWG (Str), 3/8" Stud, 1 Screw



Features

- Compact, high copper alloy terminal for joining cable to equipment pads or terminal blocks

Application

For Joining A Wide Range Of Copper Cable To Equipment Pads Or Terminal Blocks

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none">• 4 AWG• 3 AWG• 2 AWG• 1 AWG• 1/0
Conductor Size	4-1/0 AWG
Conductor - Copper Str Size Range	4 AWG-1/0
Conductor Type	CU C Str-Size

Configuration

Physical Attribute - Number of Holes	1
Physical Attribute - Number of Screws	1
Connector Type	Terminal

Current

Rating - Minimum Voltage	600
--------------------------	-----

Dimensions

Dimension - L Length Overall mm	43 mm
Dimension - Pad Width inch	0.75 in
Dimension - Height fraction	15/16
Dimension - Height inch	0.94 in
Dimension - Height mm	23.9 mm
Dimension - Hole Size fraction	27/64
Dimension - Hole Size inch	0.42 in
Dimension - Hole Size mm	11 mm
Dimension - Stud Size inch	3/8
Dimension - B Length fraction	20/29 in
Dimension - B Length inch	0.69 in
Dimension - Bolt Size fraction	3/8
Dimension - Length Overall inch	1.69 in
Dimension - N inch	0.38 in

Force Related

Installation Torque Recommended in-lb	200 LBS/in
---------------------------------------	------------

General

Trade Name	KA-LUG™
Sub Brand	KA-LUG
Physical Attribute - Screw Type	Allen
Plated	N
Type	Bolted Lugs & Terminals
UPC 12 Digit	781810363508
UPC 14 Digit GTIN	00781810363508
Hardware Type	1 / 2 "
Material	Copper
Plating Type	Unplated
UPC	781810363508

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	12000

Operational

Temperature Rating	194° F
--------------------	--------

Product Assets

[Catalog \[English\]](#)



A Hubbell brand