



KA26U, AL Set Screw Terminal, #6-2/0
AWG Str, 1-Hole, 1/4" Stud, 1 Screw, Al/Cu
Rated

By Burndy
Catalog # [KA26U](#)

Aluminum Universal Terminal, 1 Hole, 6-2/0 AWG (Str), 1/4" Stud,
1 Screw, Al/Cu Rated, Tin Plated

Features

- Dual Rated Panelboard Lugs
- High strength extruded aluminum alloy
- Electro tin-plated for low contact resistance
- Rated to 35kV

Application


For Aluminum And Copper Conductors

Specifications

Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Nominal Diameter	0.184, 0.184, 0.206, 0.232, 0.232, 0.260, 0.260, 0.292, 0.320, 0.328, 0.360, 0.368, 0.390, 0.414, 0.438
Conductor - Copper Str Size	• 14 • 5 • 4 • 3 • 2 • 1 • 1/0 • 2/0
Conductor - AL Str Size	• 14 • 4 • 3 • 2 • 1 • 1/0 • 2/0
Conductor - AL Str Size Range	14-2/0
Number Of Conductors	1



Conductor Size	6-2/0 AWG
Conductor - Copper Str Size Range	14-2/0
Conductor Type	• CU C Str-Size • AL C Str-Size

Configuration

Physical Attribute - Number of Holes	1
Physical Attribute - Number of Screws	1
Connector Type	Terminal

Dimensions

Package Length	5.500 in
Package Width	4.750 in
Package Weight	1.690 lb.
Dimension - L Length Overall mm	37 mm
Dimension - Pad Width inch	0.64 in
Dimension - Height fraction	4/5 in
Dimension - Height inch	0.80 in
Package Height	3.450 in
Dimension - Height mm	20.3 mm
Dimension - Hole Size inch	0.27 in
Dimension - Hole Size mm	7 mm
Dimension - Stud Size inch	1/4
Dimension - Width fraction	63/100 in
Dimension - Width inch	0.63 in
Dimension - Width mm	16 mm
Dimension - Bolt Hole Size inch	0.25 in
Dimension - Bolt Size fraction	1/4
Dimension - Length Overall inch	1.47 in
Dimension - D inch	0.81 in
Dimension - N inch	0.45 in

Force Related

Installation Torque Recommended in-lb	120 LBS/in
---------------------------------------	------------

General

Material - Hardware	Aluminum
Sub Brand	UNIVERSAL TERM

Physical Attribute - Screw Type	Allen
Plated	Y
Type	Bolted Lugs & Terminals
UPC 14 Digit GTIN	00781810370100
Material	Aluminum
Plating Type	Tin
UPC	781810370100

Minimum Pack Quantity	50
Carton Quantity	900
Pallet Quantity	28800

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand